## **Performance curves**

Pump **CTX65-175** 



Gene	eral o	data																						
Impeller type				Selected Ø 175 [mm]				Max. diameter 175 [mm]					lin.diame <b>30 [mn</b>		Speed 1450 [rpm]				Stages number  1					
			175	, [IIIII	11]			1/5	Įı	1		13	ווווון טכ	Щ		1450 [rpi	11]							
Operating data Capacity Head E			Efficiency				P	ower on s	shaft	Max power (	Maxpower@ratedimpeller				NPSHr Q/Qbep									
Density Kinematic viscosity Vis			Visco	Viscosity coeff. Cq				Viscosity coeff. Ch			Viscosity co	Viscosity coeff. Cη			Fluid									
1.000[kg/dm³]			1.0 [cSt]					1.00				1.	1.00			1.00			Water					
	10.0	Head				0	_																	
	-			j-		30.0	35	<u>}</u>	40.0		0									ļ ļ	Basic v	vater—	$\equiv$	
	9.0_							1			44.0										7		Ţ	
	_	[		::i		\		\-		\-		_	47.0								ļķ.			
	8.0_			- <del>  -   -  </del> -		1	1							<b>X</b>					<del></del>				1	
	0.0			1		1	-\-		\		X		\ , '			20.0		- j			1		1	
						1	\						$\mathcal{A}$					<u>. j</u>			1			
	7.0_					$\rightarrow$	$\rightarrow \downarrow$		\	<u> </u>													1	
	-									<del>/-</del> -		$\chi$							7	`\\				
	6.0_	<b>-</b>	1					_			$\overrightarrow{}$	$\overline{}$						$\nearrow$				175		
	-							\	\		<u> </u>						<u>,</u> *				1			
	5.0_		7													<u> </u>					1			
	-			_	~_				,	Ś							$\rightarrow$	-3			3			
	4.0_								/									\	<					
													<del> </del>				-   -	4		55			‡ ‡	
	3.0_	<u> </u>									$\sim$		<u></u>						†		<u> </u>			
	-	D	-1			1						;							<u> </u>		ł			
ļ.,	-															<b>1</b> 30		- <del> </del>	ļļ		ļļ.			
	2.0_	<del> </del>		<del>-</del>		+ + +	-	<del>-</del>			45.0				<del>     </del>		+		1 1	•	1		<del>+      </del>	
[m³/i	h] 0.0			5.0			10	0.0			15.0	)		20.	0	2	5.0			30.0			35.0	
	1.20_	Power																						
																					<u> </u>	175		
•	1.00_																	-	<del> </del>				1	
l .		l i i				1			-11					<u> </u>	1						1			
(	0.80	P	1 1			1 1				-				1 1								1	+	
, ا	0.60							·   - <u></u>						-}}	1			<del>+</del>		55			†	
,							<del>-</del>													55		L	ļ	
	.00.0				<u>-</u>											130				155		- L	         	
(	0.40															130				155				
(	-	D														_130				155				
[kW] (	0.40															130				155				
[kW] (	0.40															_130				155				
[kW] (	0.40	NPSHr														_130				155				
[kW] (	0.40	NPSHr														_130				55				
[kW] (	0.40	NPSHr														_130				155				
[kW](	0.40	NPSHr														_130				155				
[kW](	0.40 0.20 2.0	NPSHr														_130				55				
[kW](	0.40 0.20 2.0	NPSHr														_130				55				
[kW] (	0.40 0.20 2.0	NPSHr														_130		*		55				
[kW] (	0.40 0.20 2.0 1.0	NPSHr														_130		X		55				
[kW] (	2.0	NPSHr								Project	t							×	vice	55				
[kW] (	2.0									Project	t					_130		X		55				
[kW] (	0.40 0.20 2.0 1.0 0.0								Impe		t					_130	Diff	×		55				