Performance curves

Pump **CTX80-205**



General	data																						
Impeller type Open		Selected 2 205 [mm	์ า]		Max. diameter 205 [mm]			Min.diameter 155 [mm]				Speed 2900 [rpm]					1	Stages number 1					
Operatin	g data	l.						.1															
Capacity	<u> </u>	Head		Effic	ciency			Power	on sha	ft		Махр	ower@	rated	Impelle	er	N	IPSH	ir		Q/Q	bep	
Density 1.000[kg/dm³]		Kinematic viscosity 1.0 [cSt]			Viscosity coeff. Cq 1.00			Viscosity coeff. Ch				Viscosity coeff. Cη 1.00						luid Vate	er		.		
								1															
55.0_	Head													, ,								_	
-				40.0		45.0								‡}		· 		; 		c wate		_	
50.0_					-	7		20.0		.						·				7			
-	I			1				1	,	23.		G G	2			· † } - · · † } - ·	- () - ()		· · - · · - · · · · · · · · ·				
45.0					/	-			<u>;</u> -			7	3 - 										
-									;	ļ					`								
40.0_				\bot		+		1 .															
-				_	\uparrow	\rightarrow		/ /				\		1 1				.,		\			
35.0_	 			1		+			+	_											7	205	
-	Īii.						1	7			\sim	\downarrow							//	,			
30.0						+	-/;	<u> </u>	+				<u> </u>	\					7				
-	I - : : : : : : : : : : : : : : : : : :			-			/ <i>;</i> '-								,	>		/					
25.0	•							\longrightarrow	$\not\perp$	<u> </u>	in the state of				/	/	\rightarrow		\180				
-			·								,	\downarrow		/		/	/						
20.0											33	7	\searrow	$\stackrel{\cdot}{\searrow}$		/,				- 1 1	1		
-					- 1 1									1	~	\ 155							
l	+				- 4 5					1				1				!		- 4 1	5 1-		
[m] 15.0_	 	1 + + -			-i -i-	+			$\overline{}$			ф 1	- 1		•		 -	i ¢	, 	-i		→	
[m] 15.0_ [m³/h] 0.0	 	10.0	20	0.0	-i -i-	30.0		4	0.0		50	.0		6	60.0	1 1	7	⊤ φ 70.0	- -		80	—∳ 0.0	
[m³/h] 0.0	Power	10.0	20	0.0	 	30.0		4	0.0		50	.0		6	60.0		7	70.0	-	 			
[m³/h] 0.0		10.0	20	D.O		30.0		4	0.0		50	.0		6	60.0	+	7	70.0					
[m³/h] 0.0		10.0	20	0.0		30.0		4	0.0		50	.0		6	60.0			70.0					
[m³/h] 0.0		10.0	20	0.0		30.0		4	0.0		50	.0		6	60.0			70.0					
[m³/h] 0.0 15.00_		10.0	20	0.0		30.0		4	0.0		500	.0		6	60.0			70.0					
[m³/h] 0.0		10.0	20	0.0		30.0		4	0.0		50	.0		6	60.0	155		70.0					
[m³/h] 0.0 15.00_		10.0	20	0.0		30.0		4	0.0		50	.0		6	60.0	155		70.0					
[m³/h] 0.0		10.0	20	0.0		30.0		4	0.0		50	.0		6	60.0	155		70.0					
[m³/h] 0.0		10.0	20	0.0		30.0		4	0.0		500	.0		6	60.0	_155		70.0					
[m³/h] 0.0 15.00 10.00 5.00 [kW] 0.00	Power	10.0	20	0.0		30.0		4	0.0		50	.0		6	60.0	155		70.0					
[m³/h] 0.0 15.00 10.00 5.00 [kW] 0.00		10.0	20	0.0		30.0		4	0.0		50	.0		6	60.0	_155		70.0					
[m³/h] 0.0 15.00 10.00 5.00 [kW] 0.00	Power	10.0	20	0.0		30.0		4	0.0		50	.0		6	60.0	155		70.0					
[m³/h] 0.0 15.00 10.00 5.00 [kW] 0.00	Power	10.0	20	0.0		30.0		4	0.0		50	0.0		6	60.0	_155		70.0					
[m³/h] 0.0 15.00 10.00 5.00 [kW] 0.00 4.0 3.0	Power	10.0	20	0.0		30.0		4	0.0		50	0.0		6	60.0	_155		70.0					
[m³/h] 0.0 15.00 10.00 5.00 [kW] 0.00	Power	10.0	20	0.0		30.0		4	0.0		50	0.0		6	60.0	155		70.0					
[m³/h] 0.0 15.00 10.00 5.00 [kW] 0.00 4.0 3.0	Power	10.0	20	0.0		30.0		4	0.0		50	0.0		6	60.0	155		70.0					
[m³/h] 0.0 15.00 10.00 5.00 [kW] 0.00 4.0 3.0	Power	10.0	20	0.0		30.0		4	0.0		50	0.0		6	60.0	155		70.0					
[m³/h] 0.0 15.00 10.00 5.00 [kW] 0.00 4.0 3.0	Power	10.0	20	0.0		930.0 Project	tt.	4	0.0		50	.0		6	X	155		70.0					
[m³/h] 0.0 15.00 10.00 5.00 [kW] 0.00 4.0 2.0 [m] 1.0	Power	10.0	20	0.0		Projec	t t	4	0.0		50	.0			X			70.0					
[m³/h] 0.0 15.00 10.00 5.00 [kW] 0.00 4.0 3.0 2.0	Power	10.0	20	0.0	Impe	Projec	t t	4	0.0		50	.0			X			70.0					