Performance curves

Pump **CTX80-260**



General	data																										
Impeller typ Open	e	Select 260 [Max. c 2 60 [n.diam 5 [m				peed 450		าไ				Sta 1	ages i	numbe	er		
Operatir	ag data	200 [1			-00 [''J		10	o [iii	,		1.	700	[i þii	'1				1.					
Capacity	ig uata	Head					Efficie	ency			Po	wer or	shaft		N	Maxpo	wer@) rate	d impe	eller		NF	PSHr			Q/Qbe	p
Density 1.000[kg/		Kinematic viscosity 1.0 [cSt]				Viscosity coeff. Cq 1.00				1.0	Viscosity coeff. Ch 1.00				Viscosity coeff. Cη 1.00					Fluid Water							
	Head																										
			<u> </u>		\\							ļ			-	ļ	ļ	<u>-</u>	<u>-</u>	ļ		.	- FB	asic w	vater-	\Box	
	1																	‡						ated v			
20.0	-											<u>.</u>			j 	1		<u>.</u> 		<u> </u>	<u> </u>		<u> </u>	<u> </u>	<u> </u>		
40.0	I		1									 						÷	 								
18.0	1	1 1 1	! 									-			1	1			 	1	1						
16.0	±		i								ļ	ļ	<i></i>			ļ				ļ	ļ			ļ			
10.0.	-											, ,			j		1				ļ						
14.0	+			 								1								<u> </u>							
	1																			17	4						
12.0	ļ			i							+ /	ļ						; ; ;	; ;;	/	·				<u> </u>	260	
	1										3/							ļ	1	ļ	ļ			, /	(
10.0											4				3			11.7		-	ļ		,				
	Ĭ		 			~	\sim			4	÷	 			 		1,2	ļ ļ	ļ	ļ	·	,,,		 			
8.0										<u>`</u>	\sim						//	+			,	/					
			 									_	-		<u> </u>	ļķí					<u> </u>		 	 	 		
6.0	-	1 1													<u> </u>	_	-										
	İ														ļ	1				1	95						
[m] 4.0.	+	ļļ	ļ	j	(-							ļ								ļ	·} :						
[m] 4.0.	φ +		+ + +	b				4	P			1	-				Ψ		1			Φ-	1	1		+ φ	
[m³/h] 0.	.0	1	10.0				:	۱ 20.0	1		1	30.0			1	40.0	Υ)	1	ı	I	50.0)	1	1		60.0	
[m³/h] 0.		1 1	10.0	· · · · · · · · · · · · · · · · · · ·			2	20.0)		1	30.0		1		40.0	Υ)	'	1		50.0)		1		60.0	
[m³/h] 0.	Power	1	10.0					20.0			-1	30.0			1	40.0) 	1	L		50.0)				60.0	
[m³/h] 0.	Power		10.0					20.0				30.0			1	40.0)	1	 		50.0)		1	1		
[m³/h] 0.	Power		10.0					20.0			1	30.0			1	40.0) 	 	 		50.0)	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1		
[m³/h] 0. 5.00 4.00	Power		10.0					20.0			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	30.0				40.0))				50.0)					
[m³/h] 0.	Power		10.0					20.0				30.0				40.0	Ŷ)				50.0)					
[m³/h] 0. 5.00 4.00 3.00	Power		10.0					20.0				30.0				40.0	•)					
[m³/h] 0. 5.00 4.00	Power		10.0					20.0				30.0				40.0	•			1	50.0)					
[m³/h] 0. 5.00. 4.00 3.00.	Power		10.0					20.0				30.0				40.0	•			1							
[m³/h] 0. 5.00 4.00 3.00	Power		10.0					20.0				30.0				40.0	•			1							
[m³/h] 0. 5.00. 4.00 3.00.	Power		10.0					20.0				30.0				40.0	•			111							
[m³/h] 0. 5.00. 4.00 3.00.	Power		10.0					20.0				30.0				40.0	•			1							
[m³/h] 0. 5.00. 4.00. 3.00. 2.00. [kW] 1.00.	Power		10.0					20.0				30.0				40.0	•			1							
[m³/h] 0. 5.00. 4.00. 3.00. 2.00. [kW] 1.00.	Power		10.0					20.0				30.0				40.0	•			1							
[m³/h] 0. 5.00. 4.00. 3.00. 2.00. [kW] 1.00.	Power		10.0					220.0				30.0				40.0	•			1							
[m³/h] 0. 5.00. 4.00. 3.00. 2.00. [kW] 1.00.	Power		10.0					220.0				30.0				40.0	•										
[m³/h] 0. 5.00. 4.00. 3.00. 2.00. [kW] 1.00.	Power		10.0					220.0				30.0				40.0	•			1							
[m³/h] 0. 5.00. 4.00. 3.00. 2.00. [kW] 1.00.	Power		10.0					220.0				30.0				40.0				11							
[m³/h] 0. 5.00. 4.00. 3.00. 2.00. [kW] 1.00. 3.0.	Power		10.0					20.0				30.0				40.0	•			1							
[m³/h] 0. 5.00. 4.00. 3.00. 2.00. [kW] 1.00. 3.0.	Power		10.0					20.0	Project	at the state of th		30.0				40.0	•		Se	1.							
[m³/h] 0. 5.00. 4.00. 3.00. 2.00. [kW] 1.00. 3.0.	Power		10.0					20.0		t		30.0				40.0	•										
[m³/h] 0. 5.00. 4.00. 3.00. 2.00. [kW] 1.00. 3.0.	Power		10.0							t t		30.0				40.0	•	Diffi									